

COMBI

IP20 SURFACE DISTRIBUTION BOXES

Description: IP20 SURFACE BOX 1x2 MOD.

Reference:

BT2

Characteristics:

Product type:	Surface distribution boxes
Exterior dimensions (Height x Width x Depth):	130x50x64 mm
Dimensions of the flush-fit gap (HxWxD):	-
Number of modules:	1x2 DIN rail
Installation:	Surface
Color:	White RAL 9003
Window:	Without window
Weight (Kg):	0,08
Cable entry:	-
Components:	-
Materials:	Halogen-free plastic materials. Base: ABS

Technical data:

Degree of protection:	IP20
Resistance to impact:	IK08
Glow wire resistance:	650 °C
Ball pressure test:	70 °C
Ambient temperature range:	-25 °C / +40 °C
Maximum operating voltage:	1000 V AC / 1500 V DC
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	UNE-EN 62208 and UNE-EN 61439-1 (as applicable)
Certificates:	



Codes:


EAN:	8431044240503
Customs tariff number:	85.38.10.00
ETIM 6.0:	EC001893

COMBI

IP20 SURFACE DISTRIBUTION BOXES

Description: IP20 SURFACE BOX 1x2 MOD.

Reference: BT2



Exterior dimensions (Height x Width x Depth):

130x50x64 mm

Dimensions of the flush-fit gap (Height x Width x Depth):

-

Sustainability:

RoHS - REACH

Supply:

Supplied in individual cardboard packaging. When several items are sent together, they are bundled together with transparent film.

Packaging units: 36

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Tertiary and residential sectors. For use indoors, designed for surface installation. Flats, houses, offices, hotels, etc.