


PN 750 V Plastisolert koblingsledning

H07V-R

Plastisolert koblingsledning med flertrådet, glødd kobberleder.

Beskrivelse

Til inntrekking i røranlegg for skjult anlegg.



Standarder

Internasjonal EN 50265;HD
21.3;IEC 60332-1

Norsk NEK-HD 21.3

Kontakt

Nexans Norway AS, Div. Installasjon
Regnbueveien 7
1405 LANGHUS
Postboks: 100
Norway
Telefon: 64 86 18 00
installationcable.pc.no@nexans.com



Blyfri

Ja



Flammehemmet

Ja

PN 750 V Plastisolert koblingsledning

Egenskaper





Konstruksjonsegenskaper


Ledertype	Flertrådet, rund
Ledermateriale	Glødd kobber
Isolasjon	Polyvinylklorid - PVC
Blyfri	Ja

Bruksegenskaper

Lengde	100 m
Maks. tillatt ledertemperatur	70 °C
Flammehemmet	Ja

Produktliste

Nexans ref.	El. nummer	Produktnavn	Conductor diam. (mm)	Nom. outer diam. (mm)	Vekt (ca.) (kg/100m)	Forpakning
10022653	1050234	PN, 750 V 1x1.5 mm ² blå	1,6	3,0	2,1	Snelle
10022638	1050239	PN, 750 V 1x1.5 mm ² brun	1,6	3,0	2,1	Snelle
10022644	1050236	PN, 750 V 1x1.5 mm ² g/g	1,6	3,0	2,1	Snelle
10022622	1050231	PN, 750 V 1x1.5 mm ² grå	1,6	3,0	2,1	Snelle
10022627	1050230	PN, 750 V 1x1.5 mm ² svart	1,6	3,0	2,1	Snelle
10022657	1050274	PN, 750 V 1x10 mm ² blå	4,0	6,0	11,0	Bunt
 10022642	1050279	PN, 750 V 1x10 mm ² brun	4,0	6,0	11,0	Bunt
10022648	1050276	PN, 750 V 1x10 mm ² g/g	4,0	6,0	11,0	Bunt
 10022626	1050271	PN, 750 V 1x10 mm ² grå	4,0	6,0	11,0	Bunt
10022631	1050270	PN, 750 V 1x10 mm ² svart	4,0	6,0	11,0	Bunt
 10022658	1050284	PN, 750 V 1x16 mm ² blå	5,0	7,0	17,3	Bunt
 10022643	1050289	PN, 750 V 1x16 mm ² brun	5,0	7,0	17,3	Bunt
10022649	1050286	PN, 750 V 1x16 mm ² g/g	5,0	7,0	17,3	Bunt
10022699	1050416	PN, 750 V 1x16 mm ² g/g	5,0	7,0	17,3	Trommel
10022637	1050282	PN, 750 V 1x16 mm ² gul/rød	5,0	7,0	17,3	Bunt
10022694	1050412	PN, 750 V 1x16 mm ² gul/rød	5,0	7,0	17,3	Trommel
10022684	1050410	PN, 750 V 1x16 mm ² sort	5,0	7,0	17,3	Trommel

Nexans ref.	El. nummer	Produktnavn	Conductor diam. (mm)	Nom. outer diam. (mm)	Vekt (ca.) (kg/100m)	Forpakning
10022632	1050280	PN, 750 V 1x16 mm ² svart	5,0	7,0	17,3	Bunt
10022654	1050244	PN, 750 V 1x2.5 mm ² blå	2,0	3,6	3,3	Snelle
10022639	1050249	PN, 750 V 1x2.5 mm ² brun	2,0	3,6	3,3	Snelle
10022645	1050246	PN, 750 V 1x2.5 mm ² g/g	2,0	3,6	3,3	Snelle
10022623	1050241	PN, 750 V 1x2.5 mm ² grå	2,0	3,6	3,3	Snelle
10022628	1050240	PN, 750 V 1x2.5 mm ² svart	2,0	3,6	3,3	Snelle
10022650	1050326	PN, 750 V 1x25 mm ² g/g	6,3	8,7	26,1	Bunt
10022700	1050426	PN, 750 V 1x25 mm ² g/g	6,3	8,7	26,1	Trommel
10022695	1050425	PN, 750 V 1x25 mm ² gul/rød	6,3	8,7	26,1	Trommel
10022685	1050420	PN, 750 V 1x25 mm ² sort	6,3	8,7	26,1	Trommel
10022633	1050320	PN, 750 V 1x25 mm ² svart	6,3	8,7	26,1	Bunt
 10022651	1050336	PN, 750 V 1x35 mm ² g/g	7,4	9,8	35,0	Bunt
10022701	1050436	PN, 750 V 1x35 mm ² g/g	7,4	9,8	35,0	Trommel
10022686	1050430	PN, 750 V 1x35 mm ² sort	7,4	9,8	35,0	Trommel
10022634	1050330	PN, 750 V 1x35 mm ² svart	7,4	9,8	35,0	Bunt
10022655	1050254	PN, 750 V 1x4 mm ² blå	2,5	4,1	4,7	Bunt
10022640	1050259	PN, 750 V 1x4 mm ² brun	2,5	4,1	4,7	Bunt
10022646	1050256	PN, 750 V 1x4 mm ² g/g	2,5	4,1	4,7	Bunt
10022624	1050251	PN, 750 V 1x4 mm ² grå	2,5	4,1	4,7	Bunt
10022629	1050250	PN, 750 V 1x4 mm ² svart	2,5	4,1	4,7	Bunt
10022702	1050446	PN, 750 V 1x50 mm ² g/g	8,7	11,5	47,0	Trommel
10022696	1050442	PN, 750 V 1x50 mm ² gul/rød	8,7	11,5	47,0	Trommel
10022687	1050440	PN, 750 V 1x50 mm ² sort	8,7	11,5	47,0	Trommel
10022656	1050264	PN, 750 V 1x6 mm ² blå	3,0	4,6	6,6	Bunt
10022641	1050269	PN, 750 V 1x6 mm ² brun	3,0	4,6	6,6	Bunt
10022647	1050266	PN, 750 V 1x6 mm ² g/g	3,0	4,6	6,6	Bunt

Nexans ref.	El. nummer	Produktnavn	Conductor diam. (mm)	Nom. outer diam. (mm)	Vekt (ca.) (kg/100m)	Forpakning
10022625	1050261	PN, 750 V 1x6 mm ² grå	3,0	4,6	6,6	Bunt
10022630	1050260	PN, 750 V 1x6 mm ² svart	3,0	4,6	6,6	Bunt
10022703	1050456	PN, 750 V 1x70 mm ² g/g	9,9	12,7	66,2	Trommel
10022688	1050450	PN, 750 V 1x70 mm ² sort	9,9	12,7	66,2	Trommel